



MEET+ 200

4K USB Webcam with Microphone



Impressive Image Quality

Adopt the most advanced image DSP and 1/2.8" 8.42MP sensor, to output 3840x2160@30 UHD resolution.

Used high quality 12MP and 120-degree optical full glass lens, output ultra-high definition and crisp image.

4x digital zoom.

Support Auto Framing: Auto Framing participants at meeting start or enter, leave, or change positions. standard UVC 1.1 protocol, compatible with most VC application.

Collect the Voice Correctly

Built-in dual beam forming microphone, pick up voice at 5meters distance.

Connect Easily

USB2.0 output.

A single USB cable for video output, camera control and power supply directly, totally minimize cable clutter.

Flexible hinge design: fit for monitor, PC, tripod, wall mount and on desk mounting.

Support image flip function, camera can be installed upside down.

Specifications

Camera	Meet+ 200
Part Number	TLC-200M-U2-4K
Sensor	1/2.8 inch, 8.42MP SONY CMOS sensor
Video Format	YUY2/NV12: 1280*720@15; 1024*576@20; 640*480@30 MJPG: 3840*2160@30;2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30 H.264/H.265: 3840*2160@30; 2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30
Optical Zoom	12-megapixel fixed lens
Digital Zoom	4X
Field of Viewing	120°, distortion rate less than 4%
Iris	F=2.2
Sensor Resolution	8.42 megapixel
Control Port	USB2.0(UVC1.1/UAC1.0)
Video Port	USB2.0
S/N Ratio	>50dB
Focal Length	f=2.20mm
Minimum Lux.	0.7 lux(50 IRE Max AGC, 1/30, F1.8)
Image Parameters	
White Balance	Auto/Manual
Electronic Shutter	Auto
Mirror, Flip, Anti-flicker	50HZ/60HZ/OFF
WDR	Supported
General	
Polar distance	3~5 meters
Sensitivity	-26+2dB RL=2.2KQ Vs=2.0V
Input Voltage	4.4~5.25V@500mA(USB port)
Dimension (L x W x H)	199mmx92.5mmx65mm
Color	Silver/Black
Net Weight	0.32KG

