



# MEET+ 50

## UHD PDAF Webcam for Desktop and Small Room



PDAF(Phase Detection Auto Focus) algorithm to achieve fast and accurate focusing.

Support ePTZ electronic pan/tilt, convenient and quick to use(below 1080P).

USB2.0 output, supports MJPG, YUY2 compression format.

Supports Windows, MAC OS, Android, Linux operating systems.

Built-in 2 omnidirectional microphones, sensitivity:  $-26 \pm 2\text{dB RL} = 2.2\text{K}\Omega$  Vs = 2.0V; signal-to-noise ratio: 64dB; pickup distance: 3m.

Multiple installation ways to meet the requirements of video shooting in different occasions.

Comes with a standard USB Type-C cable(1.5 meters) for effective connection between the laptop and the camera.

LED operational indicator light automatically illuminates upon activating the image display.

## Specifications

Camera	Meet+ 50
Part Number	TLC-50-U2-4K
Sensor	1/2.55", 12.2MP UHD CMOS sensor
Horizontal View Angle	69.8°
Vertical Viewing Angle	54.59°
Diagonal Viewing Angle	81.5°
Zoom	3X digital zoom
EPTZ	Support
Output Interface	USB2.0(Type-A)
Video Format	YUY2: 640*480@30/20; 640*360@30/20
USB2.0(Type-C)	MJPG: 4000*3000P15/10; 3840*2160P30/15/10; 2592*2194P30/15/10; 2048*1536P30/15/10; 1920*1080P60/30/15/10; 1600*1200P30/15/10; 1280*720P30/15/10; 800*600P30/15/10; 640*480P30/15/10; 320*240P30/15/10;

## Image Parameters

White Balance/Exposure/Focus	Auto/Manual
Flicker	50HZ/60HZ
2D Noise Reduction	Supported
WDR/Backlight contrast	Supported
Backlight Compensation	Supported
Mirror, Flip	Supported
Microphone Pointing	Omnidirectional microphone
Sensitivity	$-26 \pm 2\text{dB RL} = 2.2\text{K}\Omega$ Vs=2.0V
Gamma/Brightness/Sharpness	Supported
Saturation/Contrast	Supported

## General

Input Voltage	USB5V
Product certification	RoHS、FCC、CE
Working Environment	Temperature: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ ; Humidity: $\leq 80\%$
Storage temperature	$-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$
Webcam Size	106mm×57.2mm×55.5mm
Package Size	144×103.5mm×50mm
Net Weight/Gross Weight	0.1kg/0.3kg
Accessories	1.5m USB2.0(A-C) cable, Manual



Video Output  
USB Type-A

