

V-JOY+ AT

NDI® AUTO-TRACKING CONTROL KEYBOARD



Features & Benefits

● Broad Compatibility

- Supports multiple protocols NDI®|HX, VISCA over IP, Serial VISCA, ONVIF, PELCO P/D,
- Users can control multiple cameras with different protocols with one keyboard, or multiple keyboards controlling one camera through a network interface.
- It has 7 camera control shortcut keys, to enable up to 255 cameras to be controlled via a keyboard.

● Intuitive and Clear Layout

- A high-definition screen to show detailed camera and control status.
- PTZF four-dimensional joystick to make smooth control of the camera's all-around rotation, zooming and focus.
- Independent layout of numeric and functional areas for clear setup and control.

● Flexible Control

- Basic pan/tilt/zoom control, PTZ control speed as well as preset can be easily accomplished.
- Auto tracking switch and set.
- 128 preset positions can be set, recalled, and cleared via the numerical button area.
- Focus, Iris, Exposure, White balance, WDR, and Backlight compensation can be set and adjusted.

● Effortless Auto-tracking Control

- Integrates auto-tracking functionality directly into the keyboard, enabling operators to activate and manage this feature with a simple button press for dynamic live operations.
- Supports precise control and customization of auto-tracking parameters, such as Tracking Switch, Target Position, PT Limitation, Initial Position, and Blackboard Area, ensuring targeted and efficient tracking.

Application



Specification

Camera	V-Joy+ AT
Part NO.	TLC-50TC(NDI)-AT
Control Ports	NDI® HX, RS232, RS422, RS485
RJ45	Ethernet port, POE (IEEE802.3af)
RS232	DB9 Male head
RS422	3.81 Spacing terminal, T+, T-, R+, R-
RS485	3.81 Spacing terminal, T+, T-
Control Protocols	NDI® HX, VISCA Serial, PELCO-P, PELCO-D, VISCA over IP, VISCA TCP, VISCA UDP, ONVIF
Upgrade Port	Type-C
LCD Screen	3.12-inch OLED screen, blue light, 256x64 pixel
Working Power	12V, 1A
Working Temperature	-10℃~50℃
Working Humidity	20%~80%
Storage Temperature	-20℃~60℃
Storage Humidity	0~90%
Dimension	320.5mmx156.5mmx18mm
Net Weight	1.05kg



Please scan with browser.

Telecam Technology Co.,Ltd

Phone number: +86 755 33275155 E-mail: sales@telycam.com

Add: 6 Floor, Building A, Shuanghuan Information Technology Industrial Park, No.8, Baoqing Rd, Longgang District, Shenzhen, 518116, China